



DG-16



SPÉCIFICATIONS TECHNIQUES

Modèle	DG-1	DG-4	DG-6	DG-9	DG-14	DG-16	DG-20	DG-30	DG-40	DG-50
Poids porteur (t)	0,7 - 1,5	2,5 - 4	4 - 6	5 - 9	7 - 14	10 - 16	14 - 20	18 - 30	25 - 40	35 - 50
Poids (kg)	75	172	290	450	642	875	1230	1850	2050	2500
Capacité (L)	25	90	150	180	300	425	500	800	900	1100
Pression hydraulique (MPa)	18 - 26	18 - 26	20 - 28	22 - 32	25 - 35	25 - 35	25 - 35	25 - 35	25 - 35	25 - 35
Débit hydraulique (l/min)	10 - 20	15 - 35	20 - 40	30 - 50	30 - 60	60 - 100	60 - 100	80 - 120	80 - 120	100 - 140
Force de fermeture (kN)	6	15	21	32	38	48	52	72	72	90
Rotation:										
Pression hydraulique (MPa)	16 - 26	18 - 26	20 - 28	22 - 32	10 - 14	10 - 14	10 - 14	10 - 14	10 - 14	10 - 16
Débit hydraulique (l/min)	5 - 18	12 - 22	15 - 25	18 - 25	20 - 30	20 - 30	20 - 30	20 - 30	20 - 30	30 - 50
Dimensions:										
A (mm)	640	1145	1355	1632	1800	1850	2050	2410	2410	2450
B (mm)	595	800	905	1035	1175	1235	1300	1485	1485	1560
Largeur (mm)	300	450	500	580	700	860	950	1115	1360	1450

Ces spécifications peuvent être changées sans avis préalable

